

Windy 278 PF



DOTACIÓN DE SERIE

- 5.209.0021 Manguera flexible 2,5 m



- 6.205.0126



- 3.754.0048



- 3.754.0049



- 3.754.0083



- 3.754.0084



- 3.754.0085



- 5.509.2176



Opcional:

- 5.212.0022 - Kit 10 filtros recolector bolsa
- 5.509.1405 - Filtro de paño para polvo fino
- 5.212.0093 - Filtro de nylon
- 5.212.0021 Filtro lavable
- 5.212.0034 Hepa filtro

Equipado con:

- 2 motores de alta eficiencia.
- Sistema de aspiración con enfriamiento by-pass.
- Sistema de limpieza de filtro.
- Depósito en plástico (PP)
- Carro anti golpes.
- Flotador para líquidos.
- Filtro de paño.
- Cable de alimentación 7,5 m.
- Ruedas sin marca.
- Accesorios Ø 40.
- Soporte práctico para accesorios.

Windy 278 PF 8.247.0002 220-240V ~	
código	50-60Hz 2 - 2000 (2400) W Motor de alta
tensión	eficiencia.
nº motores - potencia (max)	
depresión columna	22 kPa/2200 mmH2O
caudal aire	130 l/s
capacidad depósito total/polvo/liquido	78 l./35 l./48 l.
dimensiones/peso	62x51x96 cm/21,5 kg