

HMR
T.S. Total Stop

CRANKSHAFT
1450
RPM

Motor with elastic joint

CL 6.0
NEW

STANDARD EQUIPMENT

- 3.700.0030 gun M22 with swivel



- 0.966.0084 Lance M22 high/low pressure



- 3.103.0111 nozzle 050 (2015)
- 3.103.0208 nozzle 075 (1521)
- 3.103.0213 nozzle 07 (2021)



- 0.966.0086 High pressure hose 10 m - R2 5/16 (2015)
- 0.966.0112 High pressure hose 10 m - R2 3/8 (1521/2021)


Optional:

Turbo lance

- 6.602.0041 (mod. 2015)
- 6.602.0042 (mod. 1521/2021)

sand-blasting lance 500 bar

- 6.602.0028 (mod. 2015)
- 6.602.0029 (mod. 1521/2021)

- Hose reel (on request)


Equipped with:

• Integrated elastic joint, for best pump coupling • 4 poles professional electrical motor (1450 RPM) • Triplex pump with three ceramic pistons, brass linear pump head • Low voltage and delayed Total Stop • Professional pressure unloader valve • 25 Lt Diesel tank with level float • High-pressure detergent suction with proportional detergent regulation • 2 big solid wheels (Ø 260 mm) + 2 pivoting wheels with brake • No fuel indicator • Temperature setting thermostat • Safety valve • Pressure gauge • Boiler thermal protection • Contactor and motor protection with amperometric control • Independent boiler ventilation unit • Flame control (only mod. 2021) • Single central bar for vertical lifting with crane or winches • Steel frame, stainless steel cover • On request available with stainless steel coil

	HMR 2015	HMR 1521	HMR 2021
code	0.066.0071	0.066.0072	0.066.0073
operat. pressure	190/200bar	150/160bar	190/200bar
delivery rate	960 l/h	1260 l/h	1260 l/h
boiler absorbed power	6000W-400V 50Hz	6500W-400V 50Hz	8500W-400V 50Hz
motor/pump type/RPM	CL 6.0/1450	CL 6.0/1450	CL 6.0/1450
max. water inlet/outlet temp.	60/110 °C	60/110 °C	60/110 °C
dimension/weight	90x65x87cm/160 kg	90x65x87cm/160 kg	90x65x87cm/170 kg