

**HSR**

**STANDARD EQUIPMENT**

- 3.700.0030 Gun M22 - 3/8" with rotating coupling.



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0047 Nozzle type 030



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

## Optional:

- 6.608.0073 Hose reel with brake (hose not included)

**Equipped with:**

- 4 poles electrical motor (1450 RPM) with thermal protection.
- Three ceramic coated pistons.
- Built-in by-pass valve nickel plating brass linear pump head with high temperature water seals and bushing.
- Low voltage and delayed Total Stop.
- Suction and delivery S. S. valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Detergent built-in tank (4,2 lt) for indirect suction.
- Auxiliary motor for burner.
- Heavy duty steel frame.
- Hose reel with brake **(optional)**.

	<b>HSR 1509 LP</b>
code	8.630.0107
operat. pressure	150 bar-2175 psi
delivery rate	540 l/h-2.38 GPM
abs. power/voltage	3000W-230V~50Hz 1 ph
pump type/RPM	MP3.0 Ni/1450 RPM
max. water inlet/outlet temp.	60/110 °C
dimension/weight	85x65x97 cm / 113 Kg - 275 lbs