

swingo® 755 B

Battery-powered automatic scrubber drier

Key features

- • • • Agility and high performance
 - Excellent cleaning and drying result
 - Durability and robustness
 - Simplicity and easy maintenance

Perfect combination of agility and high performance

The swingo 755 B is very easy to handle and offers maximum agility for use in confined areas. The dual-axle system allows for turning the machine literally on the spot, which leads to excellent manoeuvrability in tightly congested areas. The 40 L tank volume reduces the time-consuming tank filling stops during the cleaning operation.

Excellent cleaning and drying results

The machine's patented brush follows the floor profile and delivers nearly even pressure allocation along the full working width, which leads to excellent soil removal. The patented V-shaped squeegee enables excellent water pick-up on the floor. Due to the proven three castor concept, adjustments of the squeegee are no longer necessary.

Durability and robustness

The use of high-tech material and long life components, enhance the machine's uptime, while reducing service and repair costs to a minimum.

Simple to use and easy maintenance

All components needing frequent maintenance are color-coded in yellow and can be removed easily without tools. The dashboard is self-explanatory and displays all relevant information. These features allow trouble-free operation and require minimum operator training.



swingo® 755 B



Technical data			
Theoretical performance (economy/power)	1290/1935 m²/h	Dimensions (L x W x H)	116 x 47.5 x 119.5 cm
Working width	43 cm	Turning circle	1.12 m
Squeegee width	69 cm	Brush system	1 x 43 cm
Solution tank (nominal)	40 L	Brush pressure (with/without wheel drive)	40/43 kg
Recovery tank (nominal)	40 L	Working speed (power)	3.0/4.5 km/h
Nominal consumption	900 W	Power cord length of integrated battery charger	3 m
Rated voltage	24 V	Sound level	58 dB(A)
Battery capacity	50-70 Ah/C5	Electrical protection class (BMS/non-BMS)	I/III
Battery run time (nominal)	up to 2 hours	Approvals	CE/CB Test certificate
Machine weight ready for use (economy/power)	155/160 kg		

Model	Article code
TASK® swingo® 755 B Economy	7524165
I swingo® 755 B Economy BMS	
TASK® swingo® 755 B Power	
I swingo® 755 B Power BMS	
TASK	

Accessories	Article code
PAD Drive harpoon grip 43 cm	7510829
Scrubbing brush standard 43 cm	8504750
Scrubbing brush washed concrete 43 cm	8504800
Scrubbing brush abrasive 43 cm	8504780
Filling hose with universal water coupling	8502830
TASK® IntelliDose for swingo 755/855/1255	7 51712 5
Variety of polyester and contact pads	Please refer to local price list

Additional features
BMS (Battery Management System): Integrated in the machine, the battery charger prevents deep discharging of the battery and monitors the charging process. WD (Wheel Drive): The variable working speed up to 4.5 km/h and reverse speed up to 3 km/h guarantees ergonomic and effortless utilization and increases performance compared to non-wheel drive models. IntelliFlow (Cleaning Solution Dosing): The IntelliFlow system allows for a speed-dependent supply of cleaning solution. This feature ensures that the amount of solution dosed onto the floor is always constant – no matter how fast the machine is operating. The result? No puddles in curves and turns as well as a significant saving in cleaning solution, leading to significantly increased productivity of the machine.