

## swingo® 350 B/ E

### Ultra-compact automatic scrubber drier

#### Features

- Accessibility of confined areas
- Cleaning and drying effectiveness
- Safety and simplicity
- Reliability and robustness

#### Accessibility of confined areas

Due to the very low height of the machine body and the handle which can be folded backwards the machine can reach under obstacles such as tables or racks. The roller brush, which is off set to the side, allows edge-close cleaning as well as access to corners. The wiping blade in front of the brush helps to remove the cleaning solution also when moving the machine backwards.

#### Cleaning and drying effectiveness

Compared to manual cleaning the machine delivers significantly higher hygiene levels and improves the floor appearance as well as consistency of result. This is achieved through maximum scrubbing action and the innovative V-shaped squeegee which leads to excellent drying results, even on difficult floors such as tiles with deep grouts, uneven or structured floors.

#### Safety and simplicity

Due to the system's perfect drying results the risk of slip-falls caused by wet floors is reduced to the minimum. This makes TASKI swingo 350B the perfect solution for use in day-time operations, even in high traffic areas. The ergonomically designed, height-adjustable handle with hand protection allows for the safe and comfortable use of the machine.

#### Reliability and robustness

The machine is very robust and durable and can withstand even the toughest cleaning tasks, making it one of the most reliable machines of its type in the marketplace today.



| Technical data               | TASKI®swingo® 350 B   | TASKI®swingo® 350 E   |
|------------------------------|-----------------------|-----------------------|
| Theoretical performance      | 1140m <sup>2</sup> /h | 1140m <sup>2</sup> /h |
| Working width Squeegee width | 38 cm                 | 38 cm                 |
| Solution tank/Recovery tank  | 55 cm                 | 55 cm                 |
| Rated voltage Battery        | 10 L/10 L             | 10 L/10 L             |
| capacity/autonomy Machine    | 24 V                  | 220-240V/50-60 Hz     |
| weight (ready for use)       | 25 Ah/C5-up to 1 hour | none                  |
| Dimensions (L x W x H) Brush | 67 kg                 | 46 kg                 |
| pressure (max.) Sound level  | 79 x 45 x 43 cm       | 79 x 45 x 43 cm       |
| Cord length                  | 17 kg                 | 22 kg                 |
|                              | <70 dB(A)             | <70 dB(A)             |
|                              | N/A                   | 25m                   |

| Model               | SKU Number |
|---------------------|------------|
| TASKI® swingo® 350B | 7516862    |
| I®swingo® 350B BMS  |            |
| TASKI®swingo® 350E  |            |
| I                   |            |

| Accessories                      | SKU Number |
|----------------------------------|------------|
| Cylindrical brush standard 38 cm | 7516863    |
| Cylindrical brush hard 38 cm     | 7516 8 6   |
| Active fibre padroll 38 cm       | 4          |
|                                  | 7518532    |

## Additional Features

**Brush and Squeegee Unit:** Brush and squeegee can be easily removed for cleaning. Also squeegee blade change does not require tools.

**BMS:** BatteryManagementSystem: The battery charger which is integrated in the machine, prevents deep dischargingofthebatteryand monitors the charging process

**Water regulation:** Waterflow can be individually regulated via the controls, according to degree and type of soiling.

**Handle:** The handleisergonomically shaped and height adjustable which allows comfortable use of the machine and oated